

CONSTRUCTION: 1 Conductors, E14 19/27 Silver Plated Copper, wire per M16878/4 and NEMA-HP3, Overall Silver Plated Copper Braid Shield, 90% min. braid coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers).

CONDUCTOR: 14 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Finished diameter (.095" ± .007")

COLOR CODE: 1-White

SHIELD: 36 AWG, Silver plated copper braid shield, 90% min braid coverage.


JACKET: White Polytetrafluoroethylene tape wrap jacket (PTFE)
(wall .012" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.137" Nominal

ASTRO P/N: CME4-01-STW-1419

REV	ECRN	DATE	BY	CHECK	 ASTRO	ASTRO INDUSTRIES, INC. 4403 DAYTON-XENIA ROAD DAYTON, OHIO 45432	
TOLERANCE UNLESS NOTED					TITLE: 1/C 14 SHIELDED & JACKETED HI TEMP CABLE		
DECIMALS .XX ± .XXX ±		FRACTIONS ±					
APPROVED	DATE	SCALE	DRAWING BY	DATE (YY/MM)			
		N/A	CN	17/05			

