

CONSTRUCTION: 1 Conductors, E22 19/34 Silver Plated Copper, wire per M16878/4 and NEMA-HP3, Overall Silver Plated Copper Braid Shield, 90% min. braid coverage, White PTFE Tape Wrap Jacket.

CONDUCTOR: 22 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Finished diameter (.050" ± .004")

COLOR CODE: 1-White

SHIELD: Silver plated copper braid shield 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .010" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.093" Nominal

ASTRO P/N: CME4-01-STW-2219

REV	ECRN	DATE	BY	CHECK



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED

DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	

TITLE:

**1/C 22 SHIELDED & JACKETED
 HI TEMP CABLE**

DRAWING
 NO.

SHEET
 1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE (MM/YY)
		N/A	CN	05/11