

CONSTRUCTION: 1 Conductors, E26 19/38 Silver Plated Copper, wire per NEMA HP-3, Overall Silver Plated Copper Braid Shield, 90% min. braid coverage, White PTFE Tape Wrap Jacket (minimum of 2 Contrahelically wrapped layers.)

CONDUCTOR: 26 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Finished diameter (.039" ± .004")

COLOR CODE: 1-White

DRAIN WIRE: 26 AWG, 19 strands silver plated copper per ASTM-B-298

SHIELD: 36 AWG Silver plated copper braid shield 90% min braid coverage.


JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .010" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.085" Nominal

ASTRO P/N: CME4-01-STW-2619

REV	ECRN	DATE	BY	CHECK	 <p>ASTRO INDUSTRIES, INC. 4403 DAYTON-XENIA ROAD DAYTON, OHIO 45432</p>			
A	Add NEMA HP-3 and Astro p/n	4-2-13	CN					
TOLERANCE UNLESS NOTED					TITLE: 1/C 26 SHIELDED & JACKETED HI TEMP CABLE			
DECIMALS .XX ± .XXX ±		FRACTIONS ±					DRAWING NO. SHEET 1 OF 1	
APPROVED	DATE	SCALE	DRAWING BY	DATE				
		N/A	CN	(mm/yy) 3/05				