

CONSTRUCTION: 2 conductors, E10 37/26, silver plated copper conductor, Per M16878/4B and NEMA HP-3. Overall silver plated copper braid shield, 90% min. braid coverage, White PTFE tape wrap jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 10 AWG, 37 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.139" nom.)

COLOR CODE: 1-White, 2-Black

SHIELD: 36 AWG silver plated copper braid shield 90% min coverage.


JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .014" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.309" Nominal

ASTRO PART NUMBER: CME4-02-STW-1037

REV	ECRN	DATE	BY	CHECK	 <p>ASTRO INDUSTRIES, INC. 4403 DAYTON-XENIA ROAD DAYTON, OHIO 45432</p>
A	Add NEMA	3-22-11	CN		
TOLERANCE UNLESS NOTED					TITLE: 2/C 10 SHIELDED & JACKETED HI TEMP CABLE
DECIMALS .XX ± .XXX ±		FRACTIONS ±			
APPROVED DATE SCALE DRAWING BY DATE (MMYY)					DRAWING NO. 000315-1
		N/A	CN	03/00	
					SHEET 1 OF 1