

CONSTRUCTION: 2 Conductors, E12 19/25, Silver Plated Copper, Overall Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 12 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.114" nom. ± .007")

COLOR CODE: 1-White, 2-Black

SHIELD: 36 AWG silver plated copper braid shield 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .014" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.255" Nominal

ASTRO PART NUMBER: CME4-02-STW-1219

| REV | ECRN | DATE | BY | CHECK |
|-----|------|------|----|-------|
| | | | | |
| | | | | |
| | | | | |



ASTRO INDUSTRIES, INC.

4403 DAYTON-XENIA ROAD

DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED

| DECIMALS | FRACTIONS |
|----------|-----------|
| .XX ± | ± |
| .XXX ± | |

TITLE:

2/C 12 SHIELDED & JACKETED

HI TEMP CABLE

DRAWING
NO.

090123-2

SHEET
1 OF 1

| APPROVED | DATE | SCALE | DRAWING BY | DATE |
|----------|------|-------|------------|------|
| | | N/A | CN | 1/09 |

