

CONSTRUCTION: 2 Conductors, E14 19/27, Silver Plated Copper, Per M16878/4 and NEMA-HP3 Overall Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 14 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Wire diameter (.095" ± .007")

COLOR CODE: 1-White, 2-Black

SHIELD: 36 AWG silver-plated copper braid shield 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .012" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.219" Nominal

ASTRO P/N: CME4-02-STW-1419

REV	ECRN	DATE	BY	CHECK



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED

DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	±

TITLE:

**2/C 14 SHIELDED & JACKETED
 HI TEMP CABLE**

DRAWING
 NO.

140513-1

SHEET
 1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE (yy-mm)
		N/A	CN	14/05