

CONSTRUCTION: 2 Conductors, E16 19/29, Silver Plated Copper Per M16878/4, and NEMA HP-3, Overall Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE tape wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 16 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Finished diameter (.075" nom.)

COLOR CODE: 1-White, 2-Black

SHIELD: Overall Silver Plated copper braid shield 90% min coverage.

JACKET: White PTFE tape wrap jacket (wall .012" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.184" Nominal

ASTRO P/N: CME4-02-STW-1619

REV	ECRN	DATE	BY	CHECK
A	Add NEMA HP3	8/7/13	CN	



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED	
DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	

TITLE:
2/C 16 SHIELDED & JACKETED
HI TEMP CABLE

DRAWING NO. **090127-4**

SHEET
1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE
		N/A	CN	01/09