

CONSTRUCTION: 2 Conductors, E24 19/36, Silver Plated Copper, Per M16878/4 AND NEMA HP-3, Overall Silver Plated Copper braid shield, 90% min. Coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 24 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.044" ± .004")

COLOR CODE: 1-**White**, 2-**Black**

SHIELD: 36 AWG silver plated copper braid shield 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .010" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.125" Nominal

ASTRO PART NUMBER: CME4-02-STW-2419

REV	ECRN	DATE	BY	CHECK
A	ADD NEMA HP-3	04-13-2012	CN	



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED	
DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	

TITLE:
2/C 24 SHIELDED & JACKETED
HI TEMP CABLE

DRAWING NO. **011120-1**

SHEET 1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE (MM/YY)
		N/A	CN	11/01