

**CONSTRUCTION:** 3 conductors, E10 37/26, silver plated copper conductor, Per M16878/4B and NEMA HP-3. Overall silver plated copper braid shield, 90% min. braid coverage, White PTFE tape wrap jacket (minimum of 2 contrahelically wrapped layers.)

**CONDUCTOR:** 10 AWG, 37 strands silver plated copper per ASTM-B-298

**INSULATION:** Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.139" nom.)

**COLOR CODE:** 1-White, 2-Black, 3-Red

**SHIELD:** 36 AWG silver plated copper braid shield 90% min coverage.


**JACKET:** White Polytetrafluoroethylene tape wrap jacket (wall .014" nom)

**OPERATING TEMPERATURE:** - 65°C to + 200°C

**VOLTAGE RATING:** 600 Volts

**DIAMETER:** 0.354" Nominal

**ASTRO PART NUMBER:** CME4-03-STW-1037

REV	ECRN	DATE	BY	CHECK	 <p><b>ASTRO INDUSTRIES, INC.</b> 4403 DAYTON-XENIA ROAD DAYTON, OHIO 45432</p>
<b>TOLERANCE UNLESS NOTED</b>					<b>TITLE:</b>  <b>3/C 10 SHIELDED &amp; JACKETED</b>  <b>HI TEMP CABLE</b>
DECIMALS .XX ± .XXX ±		FRACTIONS ±			
APPROVED      DATE      SCALE      DRAWING BY      DATE (MMYY)					DRAWING NO.  <b>170530-1</b>
		N/A	CN	05/17	
					SHEET 1 OF 1