

**CONSTRUCTION:** 3 Conductors, E14 19/27, Silver Plated Copper, Per Mil-W-16878/4, Rev. E Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

**CONDUCTOR:** 14 AWG, 19 strands silver plated copper per ASTM-B-298  
**INSULATION:** Polytetrafluoroethylene insulation (wall .010" nom)  
**COLOR CODE:** 1-White, 2-Black, 3-Red

**SHIELD:** 36 AWG silver-plated copper braid shield 90% min coverage.

**JACKET:** White Polytetrafluoroethylene tape wrap jacket (wall .012" nom)

**OPERATING TEMPERATURE:** - 65°C to + 200°C

**VOLTAGE RATING:** 600 Volts

**DIAMETER:** 0.247" Nominal

**ASTRO P/N:** CME4-03-STW-1419

REV	ECRN	DATE	BY	CHECK



**ASTRO INDUSTRIES, INC.**

4403 DAYTON-XENIA ROAD

DAYTON, OHIO 45432

**TOLERANCE UNLESS NOTED**

DECIMALS		FRACTIONS		
.XX	±	±		
.XXX	±			

**TITLE:**

**3/C 14 SHIELDED & JACKETED**

**HI TEMP CABLE**

DRAWING  
NO.

SHEET  
1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE
		N/A	CN	1/07