

CONSTRUCTION: 4 Conductors, E10 37/26, Silver Plated Copper, Per Mil-W-16878/4 Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 10 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.139" nom.)

COLOR CODE: 1-White, 2-Black, 3-Red, 4-Green

SHIELD: 36 AWG silver plated copper braid shield 90% min coverage.


JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .014" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.390" Nominal

ASTRO PART NUMBER: CME4-04-STW-1037

REV	ECRN	DATE	BY	CHECK	 <p>ASTRO INDUSTRIES, INC. 4403 DAYTON-XENIA ROAD DAYTON, OHIO 45432</p>
TOLERANCE UNLESS NOTED					TITLE: 4/C 10 SHIELDED & JACKETED HI TEMP CABLE
DECIMALS .XX ± .XXX ±		FRACTIONS ±			
APPROVED	DATE	SCALE	DRAWING BY	DATE (M/Y)	DRAWING NO. SHEET 1 OF 1
		N/A	CN	01/08	