

CONSTRUCTION: 4 Conductors, E14 19/27, Silver Plated Copper, Per M16878/4 and NEMA-HP3 Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 14 AWG, 19 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom)
Finished diameter (.095" ± .007")

COLOR CODE: 1-White, 2-Black, 3-Red, 4-Green

SHIELD: 36 AWG silver-plated copper braid shield 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .012" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.270" Nominal

ASTRO P/N: CME4-04-STW-1419

REV	ECRN	DATE	BY	CHECK



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED	
DECIMALS .XX ± .XXX ±	FRACTIONS ±

TITLE:
**4/C 14 SHIELDED & JACKETED
 HI TEMP CABLE**

DRAWING NO. 170530-5	SHEET 1 OF 1
------------------------------------	-----------------

APPROVED	DATE	SCALE	DRAWING BY	DATE (YY/MM)
		N/A	CN	17/05