

**CONSTRUCTION:** 4 conductors, E16 19/29, silver-plated copper Per Mil-W-16878/4, and NEMA HP-3, overall Silver-plated copper braid shield, 90% min. braid coverage, White PTFE Tape wrap jacket (minimum of 2 contrahelically wrapped layers.)

**CONDUCTOR:** 16 AWG, 19 strands silver-plated copper per ASTM-B-298

**INSULATION:** Polytetrafluoroethylene insulation (wall .010" nom)  
Finished diameter (.080" ± .007")

**COLOR CODE:** 1-White, 2-Black, 3-Red, 4-Green

**SHIELD:** 36 AWG silver-plated copper braid shield 90% min coverage.

**JACKET:** White Polytetrafluoroethylene tape wrap jacket (wall .013" nom)

**OPERATING TEMPERATURE:** - 65°C to + 200°C

**VOLTAGE RATING:** 600 Volts

**DIAMETER:** 0.233" Nominal

**ASTRO PART NUMBER:** CME4-04-STW-1619

REV	ECRN	DATE	BY	CHECK
A	ADD NEMA	01-15-2013	CN	



**ASTRO INDUSTRIES, INC.**

4403 DAYTON-XENIA ROAD

DAYTON, OHIO 45432

**TOLERANCE UNLESS NOTED**

DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	

**TITLE:**

**4/C 16 SHIELDED & JACKETED**

**HI TEMP CABLE**

DRAWING  
NO.

SHEET  
1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE (mm/yy)
		N/A	CN	8/06