

E

**CONSTRUCTION:** 4 Conductors, E24 19/36, Silver Plated Copper, Per Mil-W-16878/4, Rev.  
 Silver Plated Copper Braid Shield, 90% min. coverage, White PTFE Tape Wrap Jacket (minimum of 2 contrahelically wrapped layers.)

**CONDUCTOR:** 24 AWG, 19 strands silver plated copper per ASTM-B-298  
**INSULATION:** Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.044" ± .004")  
**COLOR CODE:** 1-White, 2-Black, 3-Red, 4-Green

**SHIELD:** 36 AWG silver plated copper braid shield 90% min coverage.

**JACKET:** White Polytetrafluoroethylene tape wrap jacket (wall .010" nom)

**OPERATING TEMPERATURE:** - 65°C to + 200°C

**VOLTAGE RATING:** 600 Volts

**DIAMETER:** 0.151" Nominal

**ASTRO PART NUMBER:** CME4-04-STW-2419

REV	ECRN	DATE	BY	CHECK



**ASTRO INDUSTRIES, INC.**  
 4403 DAYTON-XENIA ROAD  
 DAYTON, OHIO 45432

**TOLERANCE UNLESS NOTED**

DECIMALS	FRACTIONS
.XX ±	±
.XXX ±	±

**TITLE:**  
**4/C 24 SHIELDED & JACKETED**  
**HI TEMP CABLE**

DRAWING NO.

SHEET  
 1 OF 1

APPROVED	DATE	SCALE	DRAWING BY	DATE	
		N/A	CN	2/03	