

CONSTRUCTION: 4 Conductors, E26 7/34, Silver Plated Copper, overall silver plated copper braid shield, 90% min. braid coverage, White PTFE tape wrap jacket (minimum of 2 contrahelically wrapped layers.)

CONDUCTOR: 26 AWG, 7 strands silver plated copper per ASTM-B-298

INSULATION: Polytetrafluoroethylene insulation (wall .010" nom) finished diameter (.039" ± .004")

COLOR CODE: 1-White, 2-Black, 3-Red, 4-Green

SHIELD: 36 AWG silver plated copper braid shield, 90% min coverage.

JACKET: White Polytetrafluoroethylene tape wrap jacket (wall .010" nom)

OPERATING TEMPERATURE: - 65°C to + 200°C

VOLTAGE RATING: 600 Volts

DIAMETER: 0.141" Nominal

ASTRO PART NUMBER: CME4-04-STW-2607

| REV | ECRN | DATE | BY | CHECK |
|-----|------|------|----|-------|
| | | | | |
| | | | | |
| | | | | |



ASTRO INDUSTRIES, INC.
 4403 DAYTON-XENIA ROAD
 DAYTON, OHIO 45432

TOLERANCE UNLESS NOTED

| DECIMALS | FRACTIONS |
|----------|-----------|
| .XX ± | ± |
| .XXX ± | |

TITLE:

**4/C 26 SHIELDED & JACKETED
 HI TEMP CABLE**

DRAWING
 NO.

SHEET
 1 OF 1

| APPROVED | DATE | SCALE | DRAWING BY | DATE |
|----------|------|-------|------------|------|
| | | N/A | CN | 3/08 |